










Affusion pipe with cover plate - Brushed Light Gold
SERIES SPECIFIC

27 838 979
Product version from 3/2/2021




- LAMINAR FLOW, max. flow rate 15 l/min (at 3 bar)
- 3/8" shower outlet
- cover plate 240 x 60 mm
- metal shower hose 1250mm with integrated anti-twist protection
- 1/2" connection
- plug-link mounting

Intrinsic protection against back flow.

	Brushed Light Gold	27 838 979-27
	Chrome	27 838 979-00
	Brushed Platinum	27 838 979-06
	Platinum	27 838 979-08
	Dark Chrome	27 838 979-19
	Brushed Durabronze (23kt Gold)	27 838 979-28
	Matte Black	27 838 979-33
	Brushed Chrome	27 838 979-93
	Brushed Dark Platinum	27 838 979-99

Recommended miscellaneous

	<div> Concealed wall elbow - </div> <div> <ul style="list-style-type: none"> <li>•min. recess depth 90 mm</li> <li>•max. recess depth 163 mm</li> </ul> </div>	35 085 970 90
---	--	---------------

27 838 979 Product version from 3/2/2021

mm [inches]



### Flow rate chart



### Codes & Standards

DIN 4109

ISO 3822

Ü-Zeichen



## Affusion pipe with cover plate - Brushed Light Gold

SERIES SPECIFIC

27 838 979 Product version from 3/2/2021

Certificates and sustainability

LGA\_38



## Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
4	09 23 01 069 90	flow reducer	1.00	2
20	09 24 03 073 90	nipple	1.00	2
17	09 18 40 078 90	sleeve	1.00	2
1	04 12 11 073 01-27	spout	1.00	60
12	09 24 03 107 20 90	nipple	1.00	2
6	09 14 10 008 90	seal	1.00	2
14	90 14 20 026 00 90	seal	1.00	2
13	90 21 02 069 00-27	cover	1.00	30
2	90 30 02 072 00-27	Metal shower hose 1/2" x 3/8" x 1250 mm - Brushed Light Gold	1.00	30
19	09 11 02 133-27	plate	1.00	60
11	90 14 10 077 00 90	seal	1.00	2
8	09 14 03 127 90	seal	1.00	2
7	09 31 11 026 90	pin	2.00	2
9	09 11 03 046-27	connection	1.00	60
18	05 30 31 025 00 90	fixing set	1.00	2
5	90 24 03 212 00 90	nipple	1.00	2
16	09 17 20 044-27	holder	1.00	60
15	90 31 11 112 00 90	pin	1.00	2
10	90 31 11 004 00 90	pin	1.00	2
3	09 16 01 014 90	ring	1.00	2