







28 528 360



- spray head Ø 55mm
- ball-joint pivotable through 25° (in any direction)
- HORIZONTAL RAIN, max. flow rate 7 l/min (at 3 bar)
- rosette Ø 55 mm
- 1/2" connection

	Brushed Durabron (23kt Gold)	28 528 360-28
	Chrome	28 528 360-00
	Brushed Platinum	28 528 360-06
	Platinum	28 528 360-08
	Durabron (23kt Gold)	28 528 360-09
	Brushed Dark Platinum	28 528 360-99


Recommended miscellaneous

- Concealed wall elbow -** 35 085 970 90
- max. recess depth 163 mm
 - min. recess depth 90 mm



28 528 360

mm [inches]




Flow rate chart



Certificates

LGA_38652.

28 528 360



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	90 14 10 026 00 90	seal	1	2
2	09 27 35 003-28	rosette	1	60
3	09 23 30 027-28	nut	1	20
4	09 14 15 010 90	ring	1	2
5	09 16 01 014 90	ring	1	2
6	90 23 01 147 00 90	back-flow preventer	1	2
7	09 21 40 016-28	connection	1	20
8	09 14 10 015 90	seal	1	2
9	90 12 05 027 00-28	casing (completely)	1	20