

## META Wall-mounted valve cold water without pop-up waste - Brushed Light Gold

META

30 010 662 Product version from 5/1/2022



- 126mm projection
- fixed spout
- circular, air-enriched flow
- hole diameter 35 mm
- rosette Ø 60 mm
- max. flow 5.7 l/min
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

	Brushed Light Gold	30 010 662-27
	Chrome	30 010 662-00
	Brushed Platinum	30 010 662-06
	Dark Chrome	30 010 662-19
	Light Gold	30 010 662-26
	Matte Black	30 010 662-33
	Brushed Bronze	30 010 662-42
	Brushed Champagne (22kt Gold)	30 010 662-46
	Champagne (22kt Gold)	30 010 662-47
	Brushed Chrome	30 010 662-93
	Brushed Dark Platinum	30 010 662-99

### Recommended miscellaneous

#### Concealed wall elbow -

35 085 970 90



- min. recess depth 90 mm
- max. recess depth 163 mm

30 010 662 Product version from 5/1/2022  
mm [inches]



### Flow rate chart



### Codes & Standards

DIN 4109

ISO 3822

Ü-Zeichen



## META Wall-mounted valve cold water without pop-up waste - Brushed Light Gold

META


---

30 010 662 Product version from 5/1/2022

Certificates and sustainability

---

LGA\_38



**Spare parts list**

No.	Item Number	Name	Quantity used	Delivery time
2	90 27 66 019 00-27	rosette	1.00	30
4	90 28 22 385 00-27	spout	1.00	30
1	09 24 03 072 10 90	nipple	1.00	2
3	90 20 66 023 00-27	handle	1.00	30
5	09 16 03 001 90	grease	1.00	2