

Concealed thermostat with three function volume control - Brushed Bronze

SERIES SPECIFIC

36 427 970 Product version from 6/30/2022



- rotary diverter with volume control and shut-off function
- cover plate Ø 150 mm
- temperature control handle with safety limit stop at 38°C
- hot water temperature limiter, can be preset
- WRAS

	Brushed Bronze	36 427 970-42
	Chrome	36 427 970-00
	Brushed Platinum	36 427 970-06
	Platinum	36 427 970-08
	Dark Chrome	36 427 970-19
	Light Gold	36 427 970-26
	Brushed Light Gold	36 427 970-27
	Brushed Durabronze (23kt Gold)	36 427 970-28
	Matte Black	36 427 970-33
	Brushed Champagne (22kt Gold)	36 427 970-46
	Champagne (22kt Gold)	36 427 970-47
	Brushed Chrome	36 427 970-93
	Brushed Dark Platinum	36 427 970-99

Required miscellaneous



Concealed thermostat - 35 427 970 90
 • min. recess depth 80 mm
 • max. recess depth 136 mm

Recommended miscellaneous



xGRID Attachment set for integrating in the dry wall construction - 12 340 970 90

Required miscellaneous




Concealed thermostat with built-in isolators - 35 428 970 90
 • min. recess depth 80 mm
 • max. recess depth 136 mm


Required miscellaneous



xGRID Installation track 555 mm - 12 360 970 90



Flow rate chart



Codes & Standards

DIN 4109

EN 1111

ISO 3822

Scottish Water
Byelaws

UK Water Supply
Regulations

Ü-Zeichen



Concealed thermostat with three function volume control - Brushed Bronze

SERIES SPECIFIC

36 427 970 Product version from 6/30/2022

Certificates and sustainability

LGA_29	DVGW_DW- 6512DN0	WRAS_250402
--------	---------------------	-------------

