

## xTOOL Concealed thermostat without volume control 1/2" - Champagne (22kt Gold) SERIES SPECIFIC

36 501 979 Product version from 1/1/2022



- cover plate Ø 124 mm
- temperature control handle with safety limit stop at 38°C
- thermostat cartridge
- WRAS

	Champagne (22kt Gold)	36 501 979-47
	Chrome	36 501 979-00
	Brushed Platinum	36 501 979-06
	Platinum	36 501 979-08
	Durabrass (23kt Gold)	36 501 979-09
	Dark Chrome	36 501 979-19
	Light Gold	36 501 979-26
	Brushed Light Gold	36 501 979-27
	Brushed Durabrass (23kt Gold)	36 501 979-28
	Matte Black	36 501 979-33
	Brushed Bronze	36 501 979-42
	Brushed Champagne (22kt Gold)	36 501 979-46
	Brushed Chrome	36 501 979-93
	Brushed Dark Platinum	36 501 979-99

### Required miscellaneous



**xTOOL Concealed thermostat module without volume control -** 35 503 970 90  
 • max. recess depth 110 mm  
 • min. recess depth 85 mm

### Required miscellaneous



**xGRID Installation track 555 mm -** 12 360 970 90


### Recommended miscellaneous




**xGRID Attachment set for integrating in the dry wall construction -** 12 340 970 90

**xTOOL Concealed thermostat without volume control 1/2" - Champagne (22kt Gold)** SERIES SPECIFIC

36 501 979 Product version from 1/1/2022  
mm [inches]



**Flow rate chart**



**Codes & Standards**

DIN 4109	EN 1111	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen		



xTOOL Concealed thermostat without volume control 1/2" - Champagne (22kt Gold) SERIES SPECIFIC

---

36 501 979    Product version from 1/1/2022

Certificates and sustainability

---

WRAS_2011	DVGW_DW-6512DN0	LGA_29
-----------	-----------------	--------

**xTOOL Concealed thermostat without volume control 1/2" - Champagne (22kt Gold)** SERIES SPECIFIC

36 501 979 Product version from 1/1/2022

