

## xTOOL Concealed thermostat without volume control 3/4" - Dark Chrome

SERIES SPECIFIC

36 503 780



- cover plate 120 x 120 mm
- temperature control handle with safety limit stop at 38°C
- thermostat cartridge
- WRAS

	Dark Chrome	36 503 780-19
	Chrome	36 503 780-00
	Brushed Platinum	36 503 780-06
	Platinum	36 503 780-08
	Brushed Light Gold	36 503 780-27
	Brushed Durabronze (23kt Gold)	36 503 780-28
	Matte Black	36 503 780-33
	Brushed Champagne (22kt Gold)	36 503 780-46
	Champagne (22kt Gold)	36 503 780-47
	Brushed Chrome	36 503 780-93
	Brushed Dark Platinum	36 503 780-99

### Required miscellaneous



- xTOOL Concealed thermostat module without volume control -**
- max. recess depth 155 mm
  - min. recess depth 115 mm

35 503 970 90

### Required miscellaneous



**xGRID Installation track 555 mm -** 12 360 970 90

### Recommended miscellaneous



- xGRID Attachment set for integrating in the dry wall construction -**

12 340 970 90

36 503 780

mm [inches]



### Flow rate chart



### Codes & Standards

DIN 4109	EN 1111	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen		



xTOOL Concealed thermostat without volume control 3/4" - Dark Chrome

SERIES SPECIFIC

36 503 780

Certificates and sustainability

WRAS_2011	DVGW_DW- 6512DN0	LGA_29
-----------	---------------------	--------

36 503 780

