

MADISON xTOOL Concealed thermostat without volume control 3/4" - Brushed Platinum

MADISON

36 503 977







Product version up to 1/1/2022

● cover plate Ø 124 mm


● temperature control handle with safety limit stop at 38°C

● thermostat cartridge

● WRAS

	Brushed Platinum	36 503 977-06
	Chrome	36 503 977-00
	Platinum	36 503 977-08
	Durabrass (23kt Gold)	36 503 977-09
	Brushed Durabrass (23kt Gold)	36 503 977-28
	Brushed Dark Platinum	36 503 977-99

Required miscellaneous




**xTOOL Concealed thermostat module without volume control -**

●max. recess depth 110 mm

●min. recess depth 85 mm

35 503 970 90


Recommended miscellaneous



**xGRID Attachment set for integrating in the dry wall construction -**

12 340 970 90

Required miscellaneous




**xGRID Installation track 555 mm -**

12 360 970 90


# MADISON xTOOL Concealed thermostat without volume control 3/4" - Brushed Platinum

MADISON

36 503 977 Product version up to 1/1/2022  
mm [inches]



## Flow rate chart



## Codes & Standards

DIN 4109

EN 1111

ISO 3822

Scottish Water  
Byelaws

UK Water Supply  
Regulations

Ü-Zeichen




MADISON xTOOL Concealed thermostat without volume control 3/4" - Brushed  
Platinum

MADISON

36 503 977    Product version up to 1/1/2022

Certificates and sustainability

WRAS_2011	DVGW_DW- 6512DN0	LGA_29	LGA_29
-----------	---------------------	--------	--------



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
2	90 11 01 196 00 90	base	1.00	2
3	09 11 02 543-06	cover	1.00	10
4	09 31 11 048 90	pin	1.00	2
7	90 17 33 005 01-06	handle	1.00	10
6	90 21 02 112 00-06	sleeve	1.00	10
5	90 14 10 049 00 90	seal	1.00	2
1	90 15 02 063 00 90	cartridge	1.00	2