

TARA Wall valve clockwise closing 3/4" - Dark Chrome

TARA

36 608 882



- rosette Ø 55 mm
- head part with cut-to-length spindle and sleeve
- WRAS

| | | |
|---|-------------------------------------|---------------|
|  | Dark Chrome | 36 608 882-19 |
|  | Chrome | 36 608 882-00 |
|  | Brushed Platinum | 36 608 882-06 |
|  | Platinum | 36 608 882-08 |
|  | Brushed Durabronze (23kt Gold) | 36 608 882-28 |
|  | Matte Black | 36 608 882-33 |
|  | Brushed Bronze | 36 608 882-42 |
|  | Brushed Champagne (22kt Gold) | 36 608 882-46 |
|  | Champagne (22kt Gold) | 36 608 882-47 |
|  | Brushed Chrome | 36 608 882-93 |
|  | Brushed Dark Platinum | 36 608 882-99 |

Required miscellaneous

Wall valve 3/4" -


35 608 970 90



- max. recess depth 145 mm
- min. recess depth 85 mm

36 608 882

mm [inches]



Codes & Standards

| | | | |
|----------------|------|---------------------------|--------------------------------|
| ASME A112.18.1 | cUPC | Scottish Water Byelaws | UK Water Supply Regulations |
|----------------|------|---------------------------|--------------------------------|

Certificates and sustainability

| | |
|-----------|--------------|
| WRAS_2010 | IAPMO_4976 (|
|-----------|--------------|

36 608 882

