

# SERENITY SKY Rain panel for recessed ceiling installation with light - Brushed Stainless Steel

### 41 771 979

- exposed trim parts
- Rain panel with 2 different spray modes
- PURIFY RAIN, 175 x 175 mm, max. flow rate 10 l/min (at 3 bar)
- FULL RAIN, 455 x 315 mm, max. flow rate 14 l/min
- (at 3 bar) Rain panel, 600 x 420 mm
- min. recess depth 150 mm
- weight 15kg • feed pipe (hot/cold): 2x DN 20
- with anti-scale system
- Recommended control element: xTool

#### electrical:

- RGBW LED ambient lighting
- Electricity supply: 100-240 V AC, 50-60 Hz, 20 W
- system of protection: IP 65
- Feeder 3 x 1.5 mm2 NYM-J
- equipotential bonding 1 x 4mm2
- earth-leakage circuit-breaker 30 mA provided
- Provide DIN VDE 0100, Part 701 compliant safety
- zone 2 Provided by customer: Zigbee gateway
- Not suitable for use in a steam room.

includes light bulbs with a Class G energy efficiency

includes light bulbs with a Class G energy efficiency

## Required miscellaneous




	Brushed Stainless Steel	41 771 979-86
า	Chrome	41 771 979-00
	Dark Chrome	41 771 979-19
	Brushed Bronze	41 771 979-42
	Brushed Champagne (22kt Gold)	41 771 979-46
	Champagne (22kt Gold)	41 771 979-47
	Brushed Dark Platinum	41 771 979-99




# SERENITY SKY Rain panel for recessed ceiling installation with light - Brushed Stainless Steel

41 771 979 mm [inches] 1:10



## Flow rate chart





SERENITY SKY Rain panel for recessed ceiling installation with light - Brushed Stainless Steel

41 771 979



SERENITY SKY Rain panel for recessed ceiling installation with light - Brushed Stainless Steel

41 771 979

Spare parts list